

## 6 x 2 UHD HDMI Switch with Audio De-Embedding




The OR-HD62CD allows HDMI signals to be routed from any of the six connected HDMI sources for display on two connected HDMI displays. With fast switching technology this device dramatically improves the sync time to the connected HDMI displays over traditional switchers. In Matrix Mode, it allows any source to be routed independently to any output. An on-board EDID management tool (via on screen display) can be utilised for advanced audio and video signal management. In addition, this switcher also includes a cutting edge Picture in Picture (PIP) preview mode allowing the user to show 5 unselected HDMI sources in a row of small windows overlaid on top of the primary selected HDMI source video. In preview mode, both HDMI outputs show identical feeds. Further features include the ability to de-embed Hi-Definition lossless audio via a dedicated Optical output for each HDMI output, 4K resolution support, and 3D signal support.

Control is via front panel buttons, IR remote control, RS-232, Telnet or IP control for easy integration into control systems such as Demopad.

### FEATURES

- HDMI, HDCP 1.1, DVI 1.0 compliant
- Resolutions supported: HDTV - 480i to 1080p plus 1080p24fps, and 4K2K; PC - VGA to WUXGA;
- High Definition audio supported: Dolby TrueHD, Dolby Digital Plus, DTS-HD Master Audio + 7.1 Channel LPCM
- RS-232, Telnet or IP Control, IR Remote Control (supplied), Web GUI Control
- Supports audio extraction from HDMI input to Optical output, input audio sampling rate up to 192 kHz
- Ability to switch between any two sources within 1 second
- Built-in EDID Management
- Supports 3D and 4K signals
- Cutting edge Picture-in-Picture preview function

### SPECIFICATIONS



**Input:** 6x HDMI (6x HDMI Uncompressed AV and Data), 1x 3.5mm Stereo mini-jack (1x IR Proprietary Data), 1x 9pin Dsub (1x RS-232 Data), 1x RJ45 (1x IP Control), 1x USB Type A (1x Service Port Proprietary Data)

**Output:** 2x HDMI (2x HDMI Uncompressed AV and Data), 2x Toslink (2x Optical 2 Channel LPCM / Dolby Digital / Dolby Digital Plus / DTS)

**Power:** 12V/3A DC (US/EU standards, CE/FCC/UL certified)

**Dimensions:** 440mm (W) x 290mm (D) x 40mm (H)

**Gross Weight:** 5160g

**Net. Weight:** 3020g

**Packaging:** Boxed

