



NOTE:

1. Electrical properties:
1. ALL COMPONENTS ARE RoHS COMPLIANT.
2. 100% OPEN AND SHORT TEST.
3. CONDUCTOR RESISTANCE: 3 OHMS
4. INSULATION RESISTANCE: 10 MEGOHMS.
5. HI-POT: DC200V/0.01S
FC TEST 4K*2K 30Hz PASS 1080P PASS
2. RoHS compliant

MATERIAL LIST

⑤	CABLE	(7/0.10BC*1P+7/0.10BC+AM)*5PCS+7/0.12BC*4C+AM+7/0.12BC+128/0.12 AL-MG+PVC, OD: 7.3±0.1mm COLOR: BLACK	L
④	OUTER MOLD	BLACK PVC	1
③	OUTER MOLD	BLACK ABS	1
②	CONNECTOR	HDMI C-LOCK MALE, GOLD PLATED PIN, GOLD PLATED SHELL	1
①	CONNECTOR	Display Port MALE, GOLD PLATED PIN, GOLD PLATED SHELL	1
No.	PART NAME	DESCRIPTION	QTY

DISPLAYPORT : HDMI CABLE

- Gold plated DP and HDMI (360° shielded, C-LOCK) Connector
- High performed shielded cable, 30 AWG
- OFC (Oxygen free copper conductors)
- Bandwith up to 340MHz, 10.2Gbit/s
- Resolution: 3840x2160 (4K)
- Length: 5.0m

P/N: M01.40.440500

5.0m

Produced by: CECONET AG, Hintermättistrasse 1, 5506 Mägenwil, Switzerland www.ceconet.ch

LABEL

TOLERANCE	SCALE	SHEEL	DRAWN BY	DATE
.X	1 : 1	1 OF 1	Peter	31/05/2017
.XX	REV.		CHECKED BY	DATE
ANGLES	A			
	MATERIAL		THIRD ANGLE PROJECTION	
	-			

DISPLAYPORT: HDMI CABLE
male to male, black, 5M, C-Lock

PART NO.	DWG NO.
M01.40.440500	-

