



**PIN OUT**

P1	P2
1	11
3	12
5	10
7	8
9	9
11	7
13	5
15	6
17	4
19	19
2	18
4	13
6	14
8	2
10	3
12	1
14	16
16	15
18	17
20 (no connection)	20

SHELL    BRAID    SHELL

**NOTE:**

- 1. Electrical properties:**
  - ALL COMPONENTS ARE RoHS COMPLIANT.
  - 100% OPEN AND SHORT TEST.
  - CONDUCTOR RESISTANCE: 3 OHMS
  - INSULATION RESISTANCE: 10 MEGOHMS.
  - HI-POT: DC200V/0.01S  
PC TEST 4K\*2K PASS 1080P PASS
- 2. ROHS 2.0 and REACH**

**MINI DISPLAYPORT : DISPLAYPORT CABLE**

- Gold plated Mini-DP and DP Connector
- High performed shielded cable, 32 AWG
- OFC (Oxygen free copper conductors)
- Bandwith up to 270MHz, 10.8Gbit/s
- Resolution: 3840 x 2160 (4K)
- Length: 1.5m

P/N: M01.40.560150



**1.5m**

Produced by: CECONET AG, Hintermättlistrasse 1, 5506 Mägenwil, Switzerland    www.ceconet.ch

**MATERIAL LIST**

No.	PART NAME	DESCRIPTION	QTY
⑥	CABLE	[(1/0.20BC*2C+1/0.20BC*1C+AM)*5PCS+1/0.20BC*5C]+AM+D(1/0.25BC)+B(16/4/0.12ALM)+PVC, OD: 5.0MM COLOR: WHITE	L
⑤	OUTER MOLD	WHITE PVC	1
④	OUTER MOLD	WHITE ABS	1
③	INNER MOLD	LD-PE	2
②	CONNECTOR	MINIDisplayPort MALE , GOLD PLATED PIN, GOLD PLATED SHELL	1
①	CONNECTOR	DisplayPort MALE , GOLD PLATED PIN, GOLD PLATED SHELL	1

LABEL

TOLERANCE	SCALE	SHEEL	DRAWN BY	DATE
.X	1 : 1	1 OF 1	Peter	07/06/2017
.XX	REV.	A	CHECKED BY	DATE
ANGLES	MATERIAL	-	THIRD ANGLE PROJECTION	

MINI DISPLAYPORT : DISPLAYPORT CABLE	
male to male, white, 1.5M	
PART NO.	DWG NO.
M01.40.560150	-

