

PIN OUT

P1	P2
1	11
3	12
5	10
7	8
9	9
11	7
13	5
15	6
17	4
19	19
2	18
4	13
6	14
8	2
10	3
12	1
14	16
16	15
18	17
20 (no connection)	20

SHELL BRAID SHELL

NOTE:

1. Electrical properties:

1. ALL COMPONENTS ARE RoHS COMPLIANT.
2. 100% OPEN AND SHORT TEST.
3. CONDUCTOR RESISTANCE: 3 OHMS
4. INSULATION RESISTANCE: 10 MEGOHMS.
5. HI-POT: DC200V/0.01S
PC TEST 4K*2K PASS 1080P PASS

2. ROHS 2.0 and REACH

MATERIAL LIST


No.	PART NAME	DESCRIPTION	QTY
⑥	CABLE	[(1/0.20BC*2C+1/0.20BC*1C+AM)*5PCS+1/0.20BC*5C]+AM+D(1/0.25BC)+B(16/4/0.12ALM)+PVC, OD: 5.0MM COLOR: WHITE	L
⑤	OUTER MOLD	WHITE PVC	1
④	OUTER MOLD	WHITE ABS	1
③	INNER MOLD	LD-PE	2
②	CONNECTOR	MINIDisplayPort MALE , GOLD PLATED PIN, GOLD PLATED SHELL	1
①	CONNECTOR	DisplayPort MALE , GOLD PLATED PIN, GOLD PLATED SHELL	1

MINI DISPLAYPORT : DISPLAYPORT CABLE

- Gold plated Mini-DP and DP Connector
- High performed shielded cable, 32 AWG
- OFC (Oxygen free copper conductors)
- Bandwith up to 270MHz, 10.8Gbit/s
- Resolution: 3840 x 2160 (4K)
- Length: 5.0m

5.0m


P/N: M01.40.560500



M01.40.560500

Produced by: CECONET AG, Hintermättistrasse 1, 5506 Mägenwil, Switzerland www.ceconet.ch

LABEL

TOLERANCE	SCALE	SHEEL	DRAWN BY	DATE
.X	1:1	1 OF 1	Peter	07/06/2017
.XX	REV.	A	CHECKED BY	DATE
ANGLES	MATERIAL	-	THIRD ANGLE PROJECTION	

MINI DISPLAYPORT : DISPLAYPORT CABLE	
male to male, white, 5M	
PART NO.	DWG NO.
M01.40.560500	-

