

NOTE:

1. Electrical properties:
 1. ALL COMPONENTS ARE RoHS COMPLIANT.
 2. 100% OPEN AND SHORT TEST.
 3. CONDUCTOR RESISTANCE: 3 OHMS
 4. INSULATION RESISTANCE: 10 MEGOHMS.
 5. HI-POT: DC200V/0.01S
 PC TEST 4K*2K 30Hz PASS 1080P PASS
 2. ROHS 2.0 and REACH


MATERIAL LIST

⑤	CABLE	[(1/0.20BC*2C+1/0.20BC*1C+AM)*5PCS+1/0.20BC*5C]+AM+D(1/0.25BC)+B(16/4/0.12ALM)+PVC(KKE75-5001-75) OD: 5.0MM COLOR: WHITE	L
④	OUTER MOLD	WHITE PVC	1
③	OUTER MOLD	WHITE ABS	1
②	CONNECTOR	HDMI Male, Gold plated	1
①	CONNECTOR	MINI DISPLAYPORT 20P Male, Gold plated	1
No.	PART NAME	DESCRIPTION	QTY

MINI DISPLAYPORT : HDMI CABLE

- Gold plated Mini-DP and HDMI (360° shielded) connector
- High performed shielded cable, 32 AWG
- OFC (Oxygen free copper conductors)
- Bandwith up to 340MHz, 10.2Gbit/s
- Resolution: 3840x2160 (4K)
- Length: 1.5m


P/N: M01.40.540150



1.5m

Produced by: CECONET AG, Hintermättlistrasse 1, 5506 Mägenwil, Switzerland www.ceconet.ch

LABEL

TOLERANCE	SCALE	SHEEL	DRAWN BY	DATE
.X	1:1	1 OF 1	Peter	07/06/2017
.XX	REV.		CHECKED BY	DATE
ANGLES	A			
	MATERIAL		THIRD ANGLE PROJECTION	
	-			

MINI DISPLAYPORT : HDMI CABLE
 male to male, white, 1.5M

PART NO.	DWG NO.
M01.40.540150	-

