

NOTE:

- Electrical properties:
- 1.ALL COMPONENTS ARE RoHS COMPLIANT.
- 2.100% OPEN AND SHORT TEST.
- 3.CONDUCTOR RESISTANCE:3 OHMS
- 4.INSULATION RESISTANCE:10 MEGOHMS.
- 5.HI-POT:DC200V/0.01S
PC TEST 4K*2K 30Hz PASS 1080P PASS

2.ROHS 2.0 and REACH


MATERIAL LIST

⑤	CABLE	[(1/0.20BC*2C+1/0.20BC*1C+AM)*5PCS+1/0.20BC*5C]+AM+D(1/0.25BC)+B(16/4/0.12ALM)+ PVC(KKE75-5001-75) OD: 5.0MM COLOR: WHITE	L
④	OUTER MOLD	WHITE PVC	1
③	OUTER MOLD	WHITE ABS	1
②	CONNECTOR	HDMI Male, Gold plated	1
①	CONNECTOR	MINI DISPLAYPORT 20P Male, Gold plated	1
No.	PART NAME	DESCRIPTION	QTY

MINI DISPLAYPORT : HDMI CABLE

- Gold plated Mini-DP and HDMI (360° shielded) connector
- High performed shielded cable, 32 AWG
- OFC (Oxygen free copper conductors)
- Bandwith up to 340MHz, 10.2Gbit/s
- Resolution: 3840x2160 (4K)
- Length: 3.0m


P/N: M01.40.540300



3.0m

Produced by: CECONET AG, Hintermättistrasse 1, 5506 Mägenwil, Switzerland www.ceconet.ch

LABEL

TOLERANCE	SCALE	SHEEL	DRAWN BY	DATE
.X	1:1	1 OF 1	Peter	07/06/2017
.XX	REV.	A	CHECKED BY	DATE
ANGLES	MATERIAL	-	THIRD ANGLE PROJECTION	

MINI DISPLAYPORT : HDMI CABLE

male to male, white, 3M

PART NO.	DWG NO.
M01.40.540300	-

