

NOTE:

- 1. Electrical properties:**
 - 1. ALL COMPONENTS ARE RoHS COMPLIANT.
 - 2. 100% OPEN AND SHORT TEST.
 - 3. CONDUCTOR RESISTANCE: 3 OHMS
 - 4. INSULATION RESISTANCE: 10 MEGOHMS.
 - 5. HI-POT: DC200V/0.01S
PC TEST PASS 1080P PASS

2. RoHS compliant.


MATERIAL LIST

⑥	CABLE	(7/0.10BC*1P+7/0.10BC+AM)*5PCS+7/0.12BC*4C+AM+7/0.12BC+128/0.12 AL-MG+PVC, OD: 7.3±0.1mm, COLOR: BLACK	L
⑤	OUTER MOLD	BLACK ABS	1
④	OUTER MOLD	BLACK ABS	1
③	SCREW	#4-40 UNC, HOOD MOLDED: BLACK PVC	2
②	CONNECTOR	DVI MALE (24+1), GOLD PLATED PIN, GOLD PLATED SHELL	1
①	CONNECTOR	DisplayPort MALE, GOLD PLATED PIN, GOLD PLATED SHELL	1
No.	PART NAME	DESCRIPTION	QTY

DISPLAYPORT : DVI-D CABLE

- Gold plated DP and DVI-D Connector
- High performed shielded cable, 30 AWG
- OFC (Oxygen free copper conductors)
- Bandwith up to 165MHz, 4.95Gbit/s
- Resolution: 1920x1200 (WUXGA)
- Length: 1.5m

P/N: M01.40.430150




M01.40.430150

1.5m

Produced by: CECONET AG, Hintermättistrasse 1, 5506 Mägenwil, Switzerland www.ceconet.ch

LABEL

TOLERANCE	SCALE	SHEEL	DRAWN BY	DATE
.X	1:1	1 OF 1	Peter	07/04/2017
.XX	REV. A		CHECKED BY	DATE
ANGLES	MATERIAL		THIRD ANGLE PROJECTION	

DISPLAYPORT: DVI-D CABLE

male to male, black, 1.5M

PART NO.	DWG NO.
M01.40.430150	-

