

PIN ASSIGNMENT:

P1	3	1	1	1	P2
	1	2	2	2	
	2	3	3	3	
	6	9	9	9	
	4	10	10	10	
	5	11	11	11	
	9	17	17	17	
	7	18	18	18	
	8	19	19	19	
	12	24	24	24	
	10	23	23	23	
	11	22	22	22	
	15	6	6	6	
	16	7	7	7	
	17	15	15	15	
	18	14	14	14	
	19	16	16	16	
	20				
SHELL					SHELL

NOTE:

- 1. Electrical properties:**
 1. ALL COMPONENTS ARE RoHS COMPLIANT.
 2. 100% OPEN AND SHORT TEST.
 3. CONDUCTOR RESISTANCE: 3 OHMS
 4. INSULATION RESISTANCE: 10 MEGOHMS.
 5. HI-POT: DC200V/0.01S
PC TEST PASS 1080P PASS

2. RoHS compliant.

MATERIAL LIST


⑥	CABLE	(7/0.10BC*1P+7/0.10BC+AM)*5PCS+7/0.12BC*4C+AM+7/0.12BC+128/0.12 AL-MG+PVC, OD: 7.3±0.1mm, COLOR: BLACK	L
⑤	OUTER MOLD	BLACK ABS	1
④	OUTER MOLD	BLACK ABS	1
③	SCREW	#4-40 UNC, HOOD MOLDED: BLACK PVC	2
②	CONNECTOR	DVI MALE (24+1), GOLD PLATED PIN, GOLD PLATED SHELL	1
①	CONNECTOR	DisplayPort MALE, GOLD PLATED PIN, GOLD PLATED SHELL	1
No.	PART NAME	DESCRIPTION	QTY

DISPLAYPORT : DVI-D CABLE

- Gold plated DP and DVI-D Connector
- High performed shielded cable, 30 AWG
- OFC (Oxygen free copper conductors)
- Bandwith up to 165MHz, 4.95Gbit/s
- Resolution: 1920x1200 (WUXGA)
- Length: 3.0m

3.0m


P/N: M01.40.430300



M01.40.430300

Produced by: CECONET AG, Hintermättlistrasse 1, 5506 Mägenwil, Switzerland www.ceconet.ch

LABEL

TOLERANCE	SCALE	SHEEL	DRAWN BY	DATE
.X	1:1	1 OF 1	Peter	07/04/2017
.XX	REV.	A	CHECKED BY	DATE
ANGLES	MATERIAL	-	THIRD ANGLE PROJECTION	

DISPLAYPORT: DVI-D CABLE

male to male, black, 3M

PART NO.	DWG NO.
M01.40.430300	-

