

**NOTE:**

- 1. Electrical properties:**
  - 1. ALL COMPONENTS ARE RoHS COMPLIANT.
  - 2. 100% OPEN AND SHORT TEST.
  - 3. CONDUCTOR RESISTANCE: 3 OHMS
  - 4. INSULATION RESISTANCE: 10 MEGOHMS.
  - 5. HI-POT: DC200V/0.01S
  - PC TEST PASS 1080P PASS

**2. RoHS compliant.**


**MATERIAL LIST**

⑥	CABLE	(7/0.10BC*1P+7/0.10BC+AM)*5PCS+7/0.12BC*4C+AM+7/0.12BC+128/0.12 AL-MG+PVC, OD: 7.3±0.1mm, COLOR: BLACK	L
⑤	OUTER MOLD	BLACK ABS	1
④	OUTER MOLD	BLACK ABS	1
③	SCREW	#4-40 UNC, HOOD MOLDED: BLACK PVC	2
②	CONNECTOR	DVI MALE (24+1), GOLD PLATED PIN, GOLD PLATED SHELL	1
①	CONNECTOR	DisplayPort MALE, GOLD PLATED PIN, GOLD PLATED SHELL	1
No.	PART NAME	DESCRIPTION	QTY

DISPLAYPORT : DVI-D CABLE

- Gold plated DP and DVI-D Connector
- High performed shielded cable, 30 AWG
- OFC (Oxygen free copper conductors)
- Bandwith up to 165MHz, 4.95Gbit/s
- Resolution: 1920x1200 (WUXGA)
- Length: 5.0m


P/N: M01.40.430500



M01.40.430500

5.0m

Produced by: CECONET AG, Hintermättlistrasse 1, 5506 Mägenwil, Switzerland [www.ceconet.ch](http://www.ceconet.ch)

TOLERANCE	SCALE	SHEEL	DRAWN BY	DATE
.X	1:1	1 OF 1	Peter	14/07/2017
.XX	REV.	A	CHECKED BY	DATE
ANGLES	MATERIAL	-	THIRD ANGLE PROJECTION	

DISPLAYPORT: DVI-D CABLE

male to male, black, 5M

PART NO.	DWG NO.
M01.40.430500	-



LABEL