



10	Switching module	1	PCS					
9	Type B Male Shell (Bottom) Black	1	PCS					
8	Type B Male Shell (Upon) Black	1	PCS					
7	USB A Male Shell (Bottom) Black	1	PCS					
6	USB A Male Shell (Upon) Black	1	PCS	16	Label for inner box and outer carton	1	PCS	
5	Spring Lock	1	PCS	15	Inner Box 235*225*39	1	PCS	
4	SR black	3	PCS	14	ESD BAG	1	PCS	
3	Type B Male PCBA	1	PCS	13	8core+ground wire. Wire gauge, power line 22AWG+signal line 28AWG	100	mm	
2	USB A Male PCBA	1	PCS	12	Switching module Male Adapter Shell (Upon) Black	1	PCS	
1	18AWG*2C+Fiber+F+A CPR OD: (Ø04.5±0.2)mm	15000	mm	11	Switching module Male Adapter Shell (Bottom) Black	1	PCS	
ITEM	SPECIFICATIONS						Q' TY	UNIT

TOLERANCE		SCALE	SHEET	DRAWN BY	DATE	<h2 style="text-align: center;">USB Cable 3.0 A(m)-B(m)</h2> <h3 style="text-align: center;">15M</h3>	
.X	±0.25	1:1	1 OF 1	Kevin	18/05/2021		
.XX	±0.10	REV. A.1		CHECKED BY	DATE		
ANGLES	±0.5°	MATERIAL		THIRD ANGLE PROJECTION			
				PART NO.		DWG. NO.	
				M05.03.001500		-	

