

Release Notes



IMPORTANT: the firmware update cycle can take up to 10 minutes, and the device may reboot twice during update process.

Public Release

Version 1.0.2	
Features	• Video Wall Support Introduced full video wall functionality for multi-display deployments. • Bezel Compensation Added bezel correction to ensure proper image alignment across displays. • Display Rotation Enabled screen rotation at 90°, 180°, and 270° for flexible installation scenarios. • Stream Selection API Implemented a simplified API for up/down stream selection—ideal for keypad-based control systems where index management is limited. • Text Ticker (Left-to-Right Scrolling) Added ticker functionality with built-in font and language support for: Arabic, Hebrew, Persian (Farsi), Urdu, Pashto, Sindhi, Uyghur, and Dhivehi (Maldivian). • Custom Font Upload Added support for user-uploaded TTF fonts. (https://fonts.google.com/noto) <i>Note: System fonts are disabled when a custom font is active.</i> • Persistent Auto IP Auto IP addressing now persists across reboots.
Improvements	• Decoder Daisy Chaining Improved reliability and stability of decoder daisy-chain configurations.
Bug Fixes	• General stability improvements and miscellaneous bug fixes.
Known Issues	• Ticker Performance Smoothness is dependent on font complexity, size, and scroll speed. Best performance is achieved when the ticker is rendered on the decoder. • Non-English and custom fonts are limited to ~156 characters

Previous Releases

Version 1.0.1

Features

- Factory Firmware