



## Specifications

Input Ratings	Minimum	Maximum	Nominal
Voltage	100 V AC	240 V AC	115/230 V AC
Current @ 115 V AC / 120 W load	---	2.0 A rms	---
@ 230 V AC / 120 W load	---	1.0 A rms	---
Frequency	47 Hz	63 Hz	50/60 Hz

Output Ratings	
Voltage	24 V DC
Current	0 - 5 A
Power	120 W, max

Protection	
Overvoltage	140% ± 30%
Overcurrent	110% ~ 200% above rating load
Short Circuit	Hiccup / Auto-recovery

Temperature	Fahrenheit	Celsius
Operating	+32 to +104	0 to +40
Storage	-40 to +185	-40 to +85
Humidity (RH)	2% to 95%, non-condensing	

MTBF	
Full Load, MIL-HDBK-217F @ 25 °C	> 100000 hours

Application	
Environment	Indoor use only

Weight	Pounds	Kilograms
Device	1.43	0.65

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.59 x 2.63 x 6.17	41 x 67 x 157

Certification	
Device	CE, FCC, UL, CUL, TUV, CB, BSMI

## Copyright, Trademark, and Registration

© 2025 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).