



Introduction

The Atlona **AT-USB-EX350-KIT** is a data only USB 3.2 extender kit. It supports simultaneous extension of 5 Gbps USB 3.2 Gen 1 data and 480 Mbps USB 2.0 data up to 330 feet (100 meters) using a single, cost-effective Category 6A U/FTP cable.

The USB-EX350-KIT is ideal for video conferencing or remote instruction applications where high data rate USB components including laptops, computers, cameras, microphones, and speakers are in different areas of the room.

The USB-EX350-KIT is comprised of two endpoints. The host endpoint includes a USB-C port for connection to hosts such as laptops, computers, or other AV equipment that supports USB connectivity including many Omega™ Series products. The device endpoint includes three USB-A ports and one USB-C port for connection to 4K cameras, conferencing bars, microphones, speakers, and other peripherals. Bidirectional remote power allows the kit to be powered by the included power supply connected to either the host or device endpoint.

An Ethernet connection on the host endpoint provides access to advanced integration capabilities including:

- Monitor system and port status for validation and troubleshooting.
- Configure VBUS modes.
- IP to RS-232 translation supporting bi-directional serial control through the device endpoint.

The USB-EX350-KIT is a great solution for routing USB 3.2 Gen 1 data up to 5 Gbps between components at distances greater than is possible with traditional cabling.

Applications

• Education

Ideal for remote instruction applications where higher data rate USB peripherals such as 4K cameras are located at distances of up to 330 feet (100 meters) from a classroom computer or teacher laptop.

• Commercial

Provides access to higher data rate USB peripherals such as 4K cameras that are located at distances of up to 330 feet (100 meters) from video conferencing software running on a meeting/conference room computer or laptop.

Specifications

USB Capabilities	
Protocol Support	USB 2.0, USB 3.2 Gen 1 (5 Gbps)
USB 2.0 Capabilities ⁽¹⁾	Maximum hubs: 9 Maximum hub tiers: 5 (including the one in the AT-USB-EX350-KIT) Maximum devices: 7 Maximum endpoints: 14 (IN), 15 (OUT)
USB 3.2 Gen 1 Capabilities ⁽¹⁾	Maximum hub tiers: 5 (including the one in the AT-USB-EX350-KIT) Maximum endpoints: 126
USB Transfer Types	Control, Bulk, Interrupt, Isochronous
Internal Hubs	USB 2.0: 1 Hub USB 3.2 Gen 1: 1 Hub
USB Power	Host: No Power Device: max 1.5A per port, 3.2A total across all device ports
USB Device VBUS Control	Per-port settings: Follow USB Host, Always High, Always Low
Bandwidth ⁽²⁾	USB 2.0: 480 Mbps USB 3.2 Gen 1: 5 Gbps

Ethernet	
Port	1 x RJ45 on Host Endpoint
Standards and Protocols	HTTP, HTTPS, Telnet, SSH, JSON over WebSockets, TCP Proxy for RS-232, NTP
Speeds	10/100 Mbps
Addressing	DHCP, Static – selectable through built-in web server and API commands
802.1x Support	PEAP-MSCHAPv2, EAP-TLS

RS-232	
Port	1 x 3-pin captive screw on Device Endpoint
Use	External device control via TCP Proxy
Baud Rates	9600, 19200, 38400, 57600, 115200
Data Flow	Bidirectional

Distance	Feet	Meters
CAT 6a U/FTP - straight run	330	100
CAT 6a U/FTP - through patch panel/coupler	295	90
CAT 6a UTP - either straight run or through patch panel/coupler	230	70
CAT 5e UTP - either straight run or through patch panel/coupler	164	50

Indicators	
Host Endpoint	
PWR	1 x LED, green
LINK	1 x LED, green
FW ⁽³⁾	1 x LED, amber
Device Endpoint	
PWR	1 x LED, green
LINK	1 x LED, green
FW ⁽³⁾	1 x LED, amber

Specifications (continued)

Connectors (Host Endpoint)		
USB HOST (5G)	1 x USB-C, locking	
MGMT	1 x USB-C	
LAN	1 x RJ45	
HDBT-USB3	1 x RJ45	
48V - 1.36A ⁽⁴⁾	1 x 2-pin captive screw	
Connectors (Device Endpoint)		
USB DEVICES (5G)	3 x USB-A 1 x USB-C, locking	
DEBUG	1 x USB-C	
RS-232	1 x 3-pin captive screw	
HDBT-USB3	1 x RJ45	
48V - 1.36A ⁽⁴⁾	1 x 2-pin captive screw	
Environmental	Fahrenheit	Celsius
Operating Temperature	+32 to +104	0 to +40
Storage Temperature	-4 to +158	-20 to +70
Operating Humidity (RH)	20% to 90%, non-condensing	
Power		
Consumption (system)	30 W (max.)	
External Power Supply	Input: 100 - 240 V AC, 50/60 Hz Output: 48 V DC / 1.36 A	
Dimensions (H x W x D)	Inches	Millimeters
Host Endpoint	0.91 x 5.31 x 3.94	23 x 135 x 100
Device Endpoint	0.91 x 5.31 x 3.94	23 x 135 x 100
Weight	Pounds	Kilograms
Host Endpoint	0.68	0.31
Device Endpoint	0.71	0.32
Certification		
Extender Kit	CE, FCC, UKCA, RCM	
Power Supply	CE, FCC, UKCA, RCM, UL	
Compliance		
NDAA-889	Yes	
Warranty		
Device	To view the product warranty, use the following link: https://atlon.com/warranty	

Refer to footnotes on the next page.

Footnotes

- (1) A USB device can have multiple In and Out endpoints. An In endpoint sends data to a USB Host, while an Out endpoint receives data from a USB Host.
- (2) Specified bandwidth is the total available bandwidth. Actual bandwidth available for payload data will be reduced by USB and transport overhead. Practical payload data rates will be approximately 320 Mbps for USB 2.0 and 3.8 Gbps for USB 3.0.
- (3) Kit can be powered from either end.
- (4) Used to indicate the state of the HDBT-USB3 firmware.

Copyright, Trademark, and Registration

© 2025 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.